

# Stix<sup>®</sup> 800

XL Brands<sup>®</sup>

## PROFESSIONAL GRADE MULTI-PURPOSE ADHESIVE

STRONG FINAL BOND STRENGTH • LOW ODOR • SOLVENT FREE

**Stix 800** is an economical professional grade multi-purpose adhesive. It is ideal for light traffic carpet installations in offices, residential, and light commercial areas, and can also be used for mineral-fibrous-backed resilient sheet goods. **Stix 800** is a solvent-free adhesive suggested for use in occupied buildings, as it is low in odor and is environmentally safe with no hazardous ingredients. **Stix 800** is made with MicroSept™ Advanced Antimicrobial System to protect the adhesive from bacteria and fungal growth. **Stix 800** is CRI™ Green Label Plus approved for indoor air quality, SCAQMD Rule 1168 compliant and conforms to CA Section 01350.



### SUBSTRATE CONDITIONS

- Use on concrete substrates with up to 85% RH (per current ASTM F2170), and pH of 8.0–9.0.

### USE WITH

ActionBac®  
Latex unitary & foam backed  
Felt & mineral backed sheet goods

### CERTIFICATIONS

- CRI™ Green Label Plus
- LEED Credits: 2.1, 2.2: Low emitting materials

### LIMITATIONS

- Do not allow product to freeze
- Do not use on substrates that have been chemically cleaned or over treated plywood
- Not recommended for solid vinyl or vinyl foam backing
- Shelf life two years from date of manufacture, in unopened container. Store indoors at a temperature between 65-95°F.

### BEFORE YOU BEGIN:

Important: Proper substrate preparations are essential. Moisture testing must be performed and documented before installation begins. Read XL Brands Technical Bulletin titled Substrate Preparation for complete instructions before beginning installation. This document may be found at [www.xlbrands.com/resources/technical-bulletins/substrate-preparations](http://www.xlbrands.com/resources/technical-bulletins/substrate-preparations). If you have questions, contact XL Brands Technical Department at 706-508-5907 Mon-Fri, 8:00am - 5:00pm EST before you begin.

### USAGE:

Lay carpet into adhesive that is still wet enough to ensure 100% transfer to the carpet backing, and roll with a 75–100 lbs. roller. When installing over a non-porous surface, let adhesive become tacky.

### TRAFFIC:

Follow the flooring manufacturer's installation guidelines; otherwise restrict foot traffic for 24 hours after installation. No heavy traffic, rolling loads, or furniture placement for 72 hours after installation. Additional time may be necessary if the installation is over a non-porous substrate. Allow at least five days following the installation before conducting wet cleaning procedures or initial maintenance.

### OPEN TIME:

20-40 minutes, depending on substrate, ambient temperature and humidity.

### CLEAN UP:

Use a clean wet cloth to clean up adhesive while still wet. Dried adhesive may require the use of an appropriate solvent.

### DISCLAIMER:

Users should determine the suitability of this information or product for their own particular purpose or application. Manufacturer is not responsible for the misuse of this product. This Technical Data sheet and the information conveyed herein supersede all previous versions. XL Brands, MicroSept and Stix are registered trademarks of Bostik, Inc.. CRI is a registered trademark of The Carpet and Rug Institute. ActionBac is a registered trademark of Propex.

### FLOORCOVERING

Smooth back carpets  
Most commercial backings  
Rough back carpets  
Felt back sheet goods

### TROWEL RECOMMENDATION

3/32" x 3/32" x 3/32" V-notch  
1/8" x 1/8" x 1/16" V-notch  
1/8" x 1/8" x 1/16" U-notch  
1/16" x 1/16" x 1/16" SQ-Notch

### COVERAGE

10-15 square yards per gallon  
8-10 square yards per gallon  
5-8 square yards per gallon  
125-180 square feet per gallon

3/32" x 3/32" x 3/32"

1/8" x 1/8" x 1/16"

1/8" x 1/8" x 1/16"

1/16" x 1/16" x 1/16"

**IMPORTANT:** Use the specified trowel, and replace the trowel blade when worn to ensure proper spread rate.

198 Nexus Drive | Dalton, GA 30721 | tel: 800.367.4583 | fax: 706.272.5801