

Product Listing



**Carpet | Multipurpose | Resilient | Adhesive Prep | Wood
Cove Base | Seam Sealer | Specialty | Surface Prep**

XL Brands®

	Product Name	Description	Trowel	RH / pH limits
Carpet	Stix® 1100	Indoor/outdoor solvent-free carpet adhesive	4, 5, 6, 9	90% RH / 9.0 pH
	Stix® Platinum	Supreme-grade Wet-Set carpet adhesive	4, 5, 6	90% RH / 9.0 pH
Multi-purpose	GoldStix®	Premium multi-purpose adhesive	4, 5, 6, 9	90% RH / 9.0 pH
	Stix® 800	Professional-grade multi-purpose adhesive	4, 5, 6, 9	85% RH / 9.0 pH
	Stix® Iron	Multi-purpose adhesive	4, 5, 6, 9	85% RH / 9.0 pH
Cove Base	CoveStix® 4400	Lightweight cove base adhesive	8, 7	N/A
	Stix® 4500	Premium cove base adhesive	8, 7	N/A
	Stix® 4300	Professional-grade cove base adhesive	8, 7	N/A
Resilient	HydraStix® 95 Resilient	Multi-use resilient adhesive	10	95% RH / 11.0 pH
	HydraStix® 95 Aerosol	High-shear resilient adhesive	N/A	95% RH / 11.0 pH
	Dyna-Stix® VCT	High-moisture VCT adhesive	10, 11	95% RH / 10.0 pH
	Dyna-Stix® VB	HM Vinyl flooring adhesive	10	90% RH / 11.0 pH
	Stix® 5200	Rubber and resilient adhesive	5, 9, 10	85% RH / 10.0 pH
	Stix® 5300	Acrylic flooring adhesive	10, 12	90% RH / 10.0 pH
	Stix® 5500	Premium high-strength vinyl flooring adhesive	9, 10	85% RH / 10.0 pH
	Stix® 5800	Hard-setting vinyl flooring adhesive	9, 10	85% RH / 10.0 pH
	Stix® 5900	High-shear vinyl flooring adhesive	10	90% RH / 10.0 pH
Seam Sealer	Stix® Seam 10K	Universal seam sealer (passes water penetration test)	N/A	N/A
	Stix® Seam SF	Solvent-free seam sealer	N/A	N/A
	Stix® Seam Latex	Multi-use natural latex adhesive	N/A	N/A

Please read the most current TDS for detailed product instructions and limitations before using any product. TDS may be downloaded from www.xlbrands.com or by calling 706-508-5907.















	Product Name	Description	Trowel	RH / pH limits
Specialty Products	Stix® 2099	Pressure-sensitive high-moisture multi-use adhesive (not for use with vinyl backed carpet tile)	10	99% RH / 12.0 pH Resilient flooring 90% RH / 10.0 pH Sheet Vinyl
	Stix® 2121	Water-based contact cement	12	85% RH / 10.0 pH
	Stix® 2199	High moisture transitional multi-use adhesive (sheet vinyl limited to 90% RH / 10.0 pH)	10	99% RH / 12.0 pH Resilient flooring 90% RH / 10.0 pH PVC carpet tile /vinyl sheet
	Stix® 2220	Multi-use pressure sensitive adhesive		90% RH / 10.0 pH
	Stix® 2230	Multi-use pressure sensitive adhesive	10, 12	90% RH / 10.0 pH
	Stix® 2400	High moisture multi-use pressure sensitive adhesive	10	99% RH / 12.0 pH Resilient flooring 95% RH / 10.0 pH PVC carpet tile 90% RH / 10.0 pH Sheet Vinyl
	Stix Essential® RES	Aerosol spray adhesive for resilient flooring & modular carpet tile	N/A	93% RH / 11.0 pH Resilient flooring 90% RH / 10.0 pH PVC carpet tile
Adhesive Prep	DriSeal® ONYX™	Ultimate Moisture-Vapor-Barrier Coating and Primer	13	1. One-coat application: *90% RH / 8.0–12.0 pH 2. Two-coat application: *99% RH / 8.0–12.0 pH
	DriSeal® 95	Penetrating concrete sealer	12	95% RH / 11.0 pH
	TriSeal®	Adhesive residue encapsulator	12	85% RH / 10.0 pH
	Prelude®	Primer for alkaline or porous substrates	12	85% RH / 12.0 pH
Wood	Stix® 6010	High solids wood flooring adhesive	1	**90% RH / 10.0 pH
	Dyna-Stix® MSP	Modified silane polymer adhesive	2, 9	90% RH
	Dyna-Stix® WDU+	High moisture urethane wood flooring adhesive	2	***90% RH / 10.0 pH

Limitations: (read Technical Data Sheets for complete usage instructions)

* Use on approved substrates on or above grade.

**90%RH for on or above grade installations of engineered plank only, 85%RH for all other installations including below grade installations of engineered plank.

***No moisture testing required when installing engineered plank on concrete substrates above or on-grade.
Substrate must be visibly dry with no wetness or standing water.

Trowel usage description		Trowel image	Coverage
Wood flooring	1	 3/16" x 1/4" x 5/16"	50-60 sq. ft. / gallon
	2	 1/4" x 1/4"	30-35 sq. ft. / gallon
Carpet: rough back, woven, double stick carpet to cushion	3	 1/8" x 1/8" x 1/8"	45-75 sq. ft. / gallon
	4	 1/8" x 1/8" x 1/16"	45-72 ft / gallon
Carpet: smooth back, attached cushion, needle punched	5	 1/8" x 1/8" x 1/16"	70-90 sq. ft. / gallon
	6	 3/32" x 3/32" x 3/32"	90-135 sq. ft. / gallon
Cove base	7		55-60 Lin. ft. /cartridge
	8	 1/8" x 1/8"	220-250 Lin. ft. / gallon
Vinyl back carpet, carpet pad to substrate/ double stick, cork tile and underlay, VCT, rubber flooring and vinyl sheet, plank and tile over porous substrates	9	 1/16" x 1/16" x 1/16"	160-180 sq. ft. / gallon
	10	 1/16" x 1/32" x 1/32"	220-260 sq. ft. / gallon
VCT, vinyl sheet, plank and tile, rubber tiles over non-porous substrates	10	 1/16" x 1/32" x 1/32"	220-260 sq. ft. / gallon
	11	 1/16" x 1/32" x 5/64"	350-400 sq. ft. / gallon
Carpet tile, floor preparation	12	 3/8" short nap	350-400 sq. ft. / gallon
Primer Moisture-vapor-barrier coating	13	 3/8" short nap	500-800 sq. ft. / gallon
		100-200 sq. ft. / gallon	

Note: The above dimensions are given as width x depth x spacing. Spread rates vary with texture and porosity of the substrate. Trowels should be held at a consistent angle to apply adhesive. Examine notches regularly for wear. Trowel images are not to scale. Trowel recommendations are guidelines and should not supersede instructions from the floor covering manufacturer.

XL Brands®

198 Nexus Drive, Dalton, GA 30721
 Telephone: 800-367-4583
 Technical Service: 706-508-5907

Revision Date: 011823

AN ALL-NEW LINE OF SURFACE PREPARATION SOLUTIONS

XL Brands® has added a comprehensive line of Surface Preparation Solutions to our extensive line of flooring adhesives and sealants. The innovative technology, strength, and superior performance of our self-leveling underlayments, patches, and moisture-vapor-barrier coatings offer a comprehensive portfolio for a complete job with lasting results and a best-in-class warranty.

AS-100™

PREMIUM, INTERIOR/EXTERIOR ACRYLIC PRIMER

- Pigmented for application visibility
- Very low odor
- Low particle size for excellent penetration
- Can be applied to green concrete a minimum of 5 days old
- Tenacious bond strength to a variety of surfaces

Lockdown™ EVB

100% SOLIDS MOISTURE-VAPOR-BARRIER COATING

- Two-component epoxy formulation
- Single coat, rapid cure
- Low odor, solvent free, zero VOC
- Passes ASTM F3010-18

PrepStar™

HIGH-PERFORMANCE, TROWELABLE PREMIUM FINISHING UNDERLAYMENT

- Creamy smooth workability
- Exceptional coverage
- Can be retempered without the addition of water
- Excellent sandability—burnishes quickly leaving virtually no dust or trowel ridges

Rampstar™

CEMENT-BASED SCREEDING, RAMPING, AND PATCHING COMPOUND

- Can be applied over approved wood subfloors as directed
- Compatible with adhesives approved for use on concrete
- Can be retempered without the addition of water
- Install flooring in as little as one hour after installation
- Applies from a skimcoat to 2" (5.1 cm) neat and up to 5" (12.7 cm) properly extended
- Ideal base coat for resilient flooring in heavy-service environments, hospitals, and supermarkets

Grey Patch™

ECONOMICAL, CEMENT-BASED SKIMCOAT

- Workable for 15 minutes
- Compatible with XL Brands flooring adhesives

LEVEL-1™

ECONOMICAL, CEMENT-BASED, SELF-LEVELING UNDERLAYMENT

- Maintains healing properties for up to 25 minutes
- Fast return to service—walkable in just 90 minutes
- Compatible with all adhesives approved for concrete
- Can be installed over green concrete
- Can be featheredged to meet existing elevations

210™

PREMIUM, CEMENT-BASED SELF-LEVELING UNDERLAYMENT & TOPPING

- Can be installed from 1/8" to 2" (.3 to 5.1 cm) neat and to 5" (12.7 cm) properly extended
- Fast return to service—walkable in just 1 hour
- Accepts tile and stone floor coverings in as little as 4 hours
- Accepts hardwood, resilient floor coverings, and crack-isolation membranes in as little as 12 hours
- Can be left open to normal construction traffic
- Can be installed over green concrete for early construction phase applications
- Can be featheredged to meet existing elevations

AS-100™ Primer Coverage Chart				
SUBSTRATE	DILUTION	APPLICATION	COVERAGE	DRY TIME
Concrete	1:1 (AS-100™/water)	Pour and broom	300-400 sq. ft. / gal	1 hr / 24 hr max
Wood Engineered subfloors	undiluted	3/8" nap roller	300-400 sq. ft. / gal	2 hr / 24 hr max
Nonporous substrates Epoxy, ceramic, quarry tile, VCT, terrazzo	undiluted	3/8" nap roller	500 sq. ft. / gal	2 hr / 24 hr max
Highly porous substrates Gypsum screeds, mortar beds, highly porous concrete*	1st coat-1:3 (AS-100™/water)	Spray or pour and broom	150-200 sq. ft. / gal	>1 hr / 24 hr max
	2nd coat-1:1 (AS-100™/water)	Spray or pour and broom	400 sq. ft. / gal	2 hr / 24 hr max

*On highly porous substrates coverage can vary greatly

Patch Coverage Chart						
PRODUCT	SKIMCOAT	EMBOSS LEVELER	1/8"	1/4"	1/2"	MIN/MAX THICKNESS
Prepstar™	300 ft²	Coverage varies	33 ft²	N/A	N/A	Featheredge up to 1/2"
Grey Patch™	625-750 ft²	1250-1500 ft²	25-35 ft²	N/A	N/A	Featheredge up to 1/2"
Rampstar™	N/A	N/A	50 ft² Ramping: Divide by 50	25 ft² Ramping: Divide by 25	12 ft² Ramping: Divide by 12	Skimcoat up to 2"

LockDown EVB™	
POT LIFE	30 minutes
CURE TIME	Recoat 6-8 hr Prior to flooring 12 hr Final cure 48 hr
MOISTURE LIMIT	Up to 100% RH or 25 lbs vapor suppression
COVERAGE	Up to 100% Rh or 25 lbs vapor suppression
	Fully cured concrete
	75 ft² per gallon ~22 mils cured film thickness
	250 ft² per 2.5 gallons ~16 mils cured film thickness

Self-Leveling Underlayment Coverage Chart						
AREA	210™ & LEVEL-1™					
	1/8"	1/4"	3/8"	1/2"	3/4"	1"
100 ft²	2	4	6	8	12	16
500 ft²	10	20	30	40	60	80
1500 ft²	30	60	90	120	180	240
2000 ft²	40	80	120	160	240	320
3000 ft²	60	120	180	240	350	480
4000 ft²	80	160	240	320	480	640
10000 ft²	200	400	600	800	1200	1600

These charts are for reference only. Coverages may vary. Read the technical data sheets completely before choosing a product or beginning any installation. Speak with your distributor about product selection.

Surface Prep Solutions

Product Name	Description	Key Features	Size
AS-100™	Premium Interior/Exterior Acrylic Primer	<ul style="list-style-type: none"> • Can be rolled, broomed, or spray-applied, depending on application • Excellent alkali resistance • High-solids content 	<ul style="list-style-type: none"> • 1 gallon jug • 4 jugs/case • 36 cs/pallet • 5 gallon pail • 36/pallet
Lockdown™ EVB	100% Solids, Moisture-Vapor-Barrier Coating	<ul style="list-style-type: none"> • Two-component epoxy formulation • Single coat, rapid cure • Low odor, solvent free, zero VOC • Passes ASTM F3010-18 	<ul style="list-style-type: none"> • 2.5 gallon kit • 27 kits/pallet
PrepStar™	High-Performance Trowelable Premium Finishing Underlayment	<ul style="list-style-type: none"> • Bonds to a wide variety of substrates without priming or the use of an additive • Accepts many common floor coverings in as little as 15 minutes • Tenacious adhesion 	<ul style="list-style-type: none"> • 10 lb. bag • 4 bags/case • 44 cs/pallet
Rampstar™	Cement-Based Screeding, Ramping, and Patching Compound	<ul style="list-style-type: none"> • Can be used as an interior wear surface with the application of a suitable coating • Exceptional compressive strength • Tenacious adhesion 	<ul style="list-style-type: none"> • 50 lb. bag • 48/pallet
Grey Patch™	Economical Cement-Based Skimcoat	<ul style="list-style-type: none"> • Accepts flooring in as little as one hour • Requires no priming on concrete • Economical 4500 psi skimcoat that withstands heavy loads 	<ul style="list-style-type: none"> • 25 lb. bag • 90/pallet
LEVEL-1™	Economical Cement-Based Self-Leveling Underlayment	<ul style="list-style-type: none"> • Ideal for barrel-mixing or pumping applications • Can be left open to normal construction traffic for up to 12 months • Can be installed from 1/4" to 3" neat and to 5" properly extended 	<ul style="list-style-type: none"> • 50 lb. bag • 48/pallet
210™	Premium Cement-Based Self-Leveling Underlayment & Topping	<ul style="list-style-type: none"> • Ideal for barrel-mixing or pumping applications • Can be used as an underlayment or decorative topping • Maintains healing properties for up to 20 minutes 	<ul style="list-style-type: none"> • 50 lb. bag • 48/pallet



XL Brands® Surface Prep Products are specialty products and must only be used by professionals. Limitations apply. Read the technical data sheets completely before choosing a product or beginning any installation. Speak with your local distributor about product selection. XL Brands, Stix, Dyna-Stix, TriSeal, DriSeal, Prelude, GoldStix, Stix Essential, CoveStix, HydraStix, LEVEL-1, PrepStar, AS-100, 210, Rampstar, Lockdown EVB, and Grey Patch are registered trademarks of Bostik, Inc.