SCS Global Services does hereby certify that an independent assessment has been conducted on behalf of:

## **XL Brands**

198 Nexus Drive, Dalton, GA, United States

For the following product(s):

See Addendum

The product(s) meets all of the necessary qualifications to be certified for the following claim:

### FloorScore<sup>®</sup>

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom, private office, and single-family residence parameters when modeled as Flooring. Also, conforms to the SCAQMD Rule 1168 - Adhesive and Sealants (November 2022); Hong Kong Air Pollution Control (VOC) Regulation.

Standard Product Application Amount: 454 g/m<sup>2</sup>

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m<sup>3</sup> (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Methylene Chloride and Perchloroethylene are not intentionally added to certified products.

Registration # SCS-FS-02969

Valid from: January 1, 2024 to December 31, 2024

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, http://www.scsglobalservices.com/certified-green-products-guide.







2,26

Nicole Munoz, Vice President SCS Global Services 2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA

#### **Certification Addendum**

#### **XL Brands**

Certification: Registration # SCS-FS-02969 | Valid from: January 1, 2024 to December 31, 2024

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, http://www.scsglobalservices.com/certified-green-products-guide.

# Conformance:

#### Addendum FloorScore®

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom, private office, and single-family residence parameters when modeled as Flooring. Also, conforms to the SCAQMD Rule 1168 - Adhesive and Sealants (November 2022); Hong Kong Air Pollution Control (VOC) Regulation.

Standard Product Application Amount: 454 g/m<sup>2</sup>

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m<sup>3</sup> (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Methylene Chloride and Perchloroethylene are not intentionally added to certified products.

#### **Products:** Flooring Adhesive:

CoveStix 4400, Driseal 95, DriStix, DriStix 95, Dyna-Stix Wood, Dyna Stix VB, HydraStix 95 Aerosol Adhesive, HydraStix 95 Broadloom, HydraStix 95 Resilient, HydraStix 95 Transitional Adhesive, HydraStix 99 Resilient, HydraStix 99 Ultimate, Prelude, Stix 2121, Stix 2230, Stix 4500, Stix 5200, Stix 5300, Stix 5400, Stix 5402, Stix 5405, Stix 5500, Stix 5600, Stix 5800, Stix 5850, Stix 5900, Stix 6010, Stix Conductive, Stix Essential HS, Stix Essential RES, Stix Platinum, Stix Seam 10k, Triseal, Stix 2001, HM99, Stix 1100, GoldStix, Stix 700, Stix 2355, Stix 5851, XL 2000 Plus, XL 2269, XL 2500 Plus, XL 3800, PrimeStix, XL 9511 MVRS, XL Brands VS95, GreenFusion 2, Stix 2199, Stix 4300, XL 2400, Stix 5010, XL SSK-77, Stix 2099, XL 5001, Added 2/6/2024: Stix 9999

